# **DATASHEET**



# **APACHE**<sup>®</sup> conveyor checker

### The 1-scanning solution for the measurement

- Volume and weight detection as well as photograph production without stopping the conveying operation
- Flexible and modular mountability in new or existing systems
- The APACHE conveyor checker system can be used as a scanning solution for the measurement only of solely cuboid objects
- The identification of the objects to be measured via automatic or manual barcode reading, transponders (RFID) or via a direct connection to the material flow control of the conveyor system.
- Transfer of the data to the customer data base
  length, width, height, photo and weight are automatically transferred to your system through flexible interfaces
- Checking the fill level of containers



## Technical Data

#### **Product Dimensions**

The dimensions of an APACHE conveyor checker system depend on the mount of choice and the size of the object to be measured.

#### Maximum package size\*

350 cm x 250 cm x 280 cm

#### Division\*

2 cm / 2 cm / 1 cm

#### Minimum package size\*

20 cm x 20 cm x 10 cm

#### Movement speed

ca. 0,2 – 0,8 m/sec.

#### Scale

The technical data of the weighing device can be found in the manufacturer's documentation

#### **Power Requirements**

200-250 VAC 16 A

#### **Laser Safety Class**

1

(safety measures are unnecessary even in case of continuous irradiation)

\*LxWxH

Boelstrasse 7 57518 Alsdorf Germany

Phone: +49 2741-9377-0 Fax.: +49 2741-9377-29

eMail: info@akl-tec.de





Stand: 15.01.18 www.akl-tec.de