DATASHEET



APACHE[®] flying forklift

A new dimension of drive-by measuring and weighing

- Dynamic system for volume and weight detection as well as photo creation without stopping, simply while the forklift is passing through
- The flying forklift measures the cargo with 3 laser scanners while it is driving through and simultaneously detects the forklift with a camera
- After the identification of the forklift, it is blurred out from the measurement and the relevant freight data is determined
- Identification of the cargo is performed on entrance underneath the scanners through barcode, transponder or direct connection with material flow control
- Transfer of the data to the customer data base length, width, height, photo and weight are automatically transferred to your system through defined interfaces
- Quick master data collection without a delay through drive by measurement
- The entire measurement data is legally relevant due to the conformity assessment of the measurement system and can therefore be used for billing purposes
- The detection of freight that has been under-declared leads to a quick amortisation of the investment



Boelstrasse 7 57518 Alsdorf Germany

Phone: +49 2741-9377-0 Fax.: +49 2741-9377-29

eMail: info@akl-tec.de



Find us on facebook apache.akl



Technical data

Product Dimensions

The dimensions of an APACHE portal system depend on the mount of choice (ceiling, wall, free-standing).

Max. Measure Area* 200 cm x 200 cm x 280 cm Division*

2 cm / 2 cm / 2 cm **Minimum package size*** 20 cm x 20 cm x 10 cm

Movement speed

forklift ca. 0,7 m/sec.

Scale

Weighing forks or platform scale (size according to requirement)

Power Requirements 200-250 VAC 16 A Laser Safety Class

1

(safety measures are unnecessary even in case of continuous irradiation)

*L x W x H



Any Questions? sales@akl-tec.de

Stand: 13.12.17

www.akl-tec.de